



UNIVERSAL PRIMER

MULTI-SUBSTRATE PRIMER FOR POROUS AND IMPERMEABLE WALL AND FLOOR SUBSTRATES

SPRAYABLE INTERIOR-EXTERIOR

TECHNICAL DEFINITION.

Primer for preparation of permeable and impermeable substrates.

Improves adhesion and regulates the porosity, limits bubbling and shading.

Milky white liquid which becomes transparent when dry.

Undiluted application with a wide or narrow brush, roller or mechanically (gun).

TECHNICAL FEATURES.

- Dry extract: 25% (aqueous solution).
- Density: 1.05 kg/l.
- pH: 8
- VOC: < 1g/l.

PACKAGINGS.

10-litre bucket.

SUITABLE SUBSTRATES.

INTERIOR AND EXTERIOR FLOORS.

- Cement screed, slab.
- Concrete slab.
- Tiles.
- Paint.
- Asphalt coating.
- Traces of glues.
- Wooden boards (particle board, waterproof particle board, plywood).

INTERIOR AND EXTERIOR WALLS.

- Cement coating.
- Concrete.
- Aerated concrete.
- Silicate stone.
- Plaster.
- Plaster board.
- Plaster block.
- Brick.
- Paint.
- Tiles.
- Wooden boards (particle board, waterproof particle board, plywood).
- Traces of glues.

STORAGE.

12 months frost-free and away from high heat in original unopened packaging.

INSTRUCTIONS FOR USE

PRECAUTIONS FOR USE.

Do not apply in temperatures < + 5°C and > +30°C. Do not apply to surfaces that are too hot or in full sun. Do not apply to frozen surfaces. Do not apply directly to floors which are permanently wet or subject to rising damp. Shake the primer before use to homogenise the solution.

SURFACE PREPARATION BEFORE APPLICATION.

The substrates must be dry, clean, hard and free of any trace of separating agents and non-adhesive areas, dust-free.

On highly permeable substrates, apply until the substrate is saturated.

APPLICATION.

Undiluted application with a wide or narrow brush, roller or mechanically (gun).

CLEANING OF TOOLS.

Clean in water immediately after use.

DRYING TIME.

From 30 minutes to 2 hours depending on the amount applied, the substrate and according to the temperature, relative humidity and aeration of the room.

Variable en fonction de la porosité du support : de 50 à 150 g/m².

CONSUMPTION.

Variable depending on the porosity of the substrate: from 50 to 150g/m².

COVERINGS.

Floor levelling compounds, tile adhesives, coatings, paint.

ADVANTAGES

- Multiple substrates.
- Floors and walls.
- Interior and exterior
- Sprayable.
- Quick drying.

VOC CONTENT

EU limit value for this product (cat A/g): 30 g/l. (2010)

This product contains a maximum of 1g/l.

